

# SAFETY DATA SHEET

PPE
Revision Number: 1
ARATION AND OF THE
Beck/Arnley Power Steering Fluid
252-0020
Not available
<u>se</u>
Automotive Lubricant
No information available
Beck/Arnley 2375 Midway Lane Smyrna, TN 37167 Telephone: 615-220-3200 Email: beckcustomerservice@fmmotorparts.com

24 Hour Emergency Phone Number:

INFOTRAC 1-800-535-5053

# 2. HAZARDS IDENTIFICATION

# 2.1 Classification

This material is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) and WHMIS 2015

Acute toxicity - Oral	Not classified
Acute toxicity - Dermal	Not classified
Acute Toxicity - Inhalation (Gases)	Not classified
Acute Toxicity - Inhalation (Vapors)	Not classified
Acute Toxicity - Inhalation (Dusts/Mists)	Not classified
Skin corrosion/irritation	Not classified
Serious eye damage/eye irritation	Not classified
Respiratory sensitization	Not classified
Skin sensitization	Category 1
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
Specific target organ toxicity (single exposure)	Not classified
Specific target organ toxicity (repeated exposure)	Not classified
Aspiration toxicity	Not classified
Physical Hazards	Not classified
Physical Hazards	None

# 2.2. Label elements



Signal word	Warning
Hazard statements	H317 - May cause an allergic skin reaction
Precautionary Statements - Prevention:	P261 - Avoid breathing dust, fume, gas, mist, vapors or spray P280 - Wear protective gloves P272 - Contaminated work clothing should not be allowed out of the workplace
Precautionary Statements - Response:	P321 - Specific treatment (see supplemental first aid instructions on this label) P362 + P364 - Take off all contaminated clothing and wash it before reuse
Skin	P302 + 352 - IF ON SKIN: Wash with plenty of soap and water P363 - Wash contaminated clothing before reuse P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention
Precautionary Statements - Disposal:	P501 - Dispose of contents/ container to an approved waste disposal plant
Hazards not otherwise classified (HNOC)	Not applicable

# 2.3 Other information

Other hazards

Unknown acute toxicity

May be harmful in contact with skin

6.27 % of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

# 3.1 Substances Not applicable

# 3.2 Mixtures

#### **Hazardous Components**

Chemical Name	CAS No.	Weight-%	US GHS Classification	Notes
Thio Alkyl long chain alkyl ester	93882-40-7	<1	Eye Irrit. 2 (H319) Skin Sens. 1 (H317)	

# **Non-Hazardous Components**

Chemical Name	CAS No.	Weight-%
Lubricating Base Stocks	Mixture	>95

# 4. FIRST AID MEASURES

# 4.1 4.1 First Aid Measures

General Advice	If symptoms persist, call a physician. Take a copy of the Safety Data Sheet when going for medical treatment.
Eye Contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If eye irritation persists: Get medical advice/attention.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash contaminated clothing before re-use. Call a physician immediately.
Inhalation	Move to fresh air in case of accidental inhalation of vapors. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Call a physician immediately.
Ingestion	Do not induce vomiting without medical advice. If vomiting occurs naturally, have casualty lean forward to reduce the risk of aspiration. If symptoms persist, call a physician.
Protection of First-aiders	Use personal protective equipment. Avoid contact with eyes, skin and clothing.
4.2 4.2 Most important symptoms	and effects, both acute and delayed
Symptoms	No information available.
4.3 4.3 Indication of any immediate	e medical attention and special treatment needed
Notes to Physician	Treat symptomatically.

. FIRE-FIGHTING MEASURES

Flammable Properties	NFPA: Class IIIB Combustible Liquid
5.1 Suitable Extinguishing Media:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment
Unsuitable Extinguishing Media:	Do not use a solid water stream as it may scatter and spread fire.
5.2 Specific Hazards Arising from the Chemical	Keep product and empty container away from heat and sources of ignition.
Hazardous combustion products:	During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and / or irritating. Combustion products may include and are not limited to: Carbon oxides Oxides of Magnesium Nitrogen oxides (NOx) Oxides of Phosphorus Sulphur oxides Zinc oxides
5.3 Protective Equipment and Precautions for Firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# 6. ACCIDENTAL RELEASE MEASURES

# 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists. Use personal protection recommended in Section 8. Ensure adequate ventilation. Remove all sources of ignition.
6.2 Environmental Precautions	
Environmental Precautions	See section 12 for additional ecological information. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system. Large Spills: Dike far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.
6.3 Methods and material for conta	inment and cleaning up
Methods for Clean-up	Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceus earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Spill Management	
LARGE SPILLS	Eliminate sources of ignition. Prevent additional discharge of material if possible to do so without hazard. For small spills implement cleanup procedures; for large spills implement cleanup procedures and, if in public area, keep public away and advise authorities. Also, if this product is subject to CERCLA reporting (see Section 15 Regulatory Information) notify the National Response Center.
WATER SPILLS	Prevent liquid entering sewers, watercourses, or low areas. Contain spilled liquid with sand or earth. Recover by pumping or with suitable absorbent. If liquid is too viscous for pumping, scrape up. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

# . HANDLING AND STORAGE

7.1. Precautions for safe handling	
Handling	Do not breathe dusts or mists. Avoid contact with eyes, skin and clothing. Wear protective gloves/protective clothing/eye protection/face protection. Use personal protection recommended in Section 8. Wash hands thoroughly after handling. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. Should not be released into the environment.
Safe Handling Advice	Wear personal protective equipment. Do not breathe vapors or spray mist. Use product only in closed system.
7.2. Conditions for safe storage, including any incompatibilities	
Storage	Keep in properly labeled containers. Keep container tightly closed in a dry and well-ventilated place.
Technical measures/Precautions	Ensure adequate ventilation. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.
Incompatible Materials and/or Coatings	No information available

# 3. EXPOSURE CONTROLS/PERSONAL PROTECTION

# 8.1 Control parameters

Exposure Guidelines

This product does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies.

#### **Other Exposure Guidelines (If Generated)**

Chemical Name	OSHA PEL	ACGIH TLV	ACGIH OEL (STEL)	NIOSHT REL TWA	ILA IHG	ILA ROEG	ILA Internal Exposure Limit
Oil mist, mineral	TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>		TWA 5 mg/m <sup>3</sup> ST 10 mg/m <sup>3</sup>			

#### 8.2 Exposure controls

Appropriate engineering controls Ensure adequate ventilation, especially in confined areas. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

### Personal Protective Equipment

	industrial settings. If splashes are likely to occur wear tight fitting safety goggles and/or face-shield.
Skin protection	Wear protective gloves/clothing. Long sleeved clothing. Choose the appropriate protective clothing / gloves based on the tasks being performed to avoid exposed skin surfaces. <b>Glove Type:</b> Neoprene, Nitriles
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
General Hygiene Considerations	Clean equipment, work area and clothing regularly. When using, do not eat, drink or smoke.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

# 9.1. Information on basic physical and chemical properties

Appearance Physical State Odor
Odor Threshold
pH Malting point (malting rough
Melting point / melting range
Boiling point / boiling range
Flash Point
Evaporation Rate
Flammability Limit in Air
Explosion Limits
Vapor Pressure
Vapor Density (Air)
Density
Solubility
Partition Coefficient (n-octanol/water)
Autoignition Temperature
Decomposing Temperature
Viscosity
viscosity

### Amber / Clear Liquid Mild No information available Not applicable Not applicable No information available 217 °C / 423 °F COC ASTM D92 No information available 0.86 g/cm<sup>3</sup> @15°C No information available No information available No information available No information available @ 40C = 38.27 cSt; @ 100C = 7.65 cSt

# Other Information

# 10. STABILITY AND REACTIVITY

10.1 Reactivity	
Reactivity	The product is chemically stable
10.2 Chemical stability	
Chemical Stability	Stable under recommended storage conditions.
10.3 Possibility of Hazardous Reactions	
Possibility of Hazardous Reactions	None under normal processing.
Hazardous Polymerization	Hazardous polymerisation does not occur.
10.4 Conditions to Avoid	
Conditions to Avoid	Heat, flames and sparks.

#### **10.5 Incompatible Materials**

Incompatible Materials

10.6 Hazardous Decomposition Products

Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and vapors.

Strong oxidizing agents.

# 11. TOXICOLOGICAL INFORMATION

# 11.1 Information on likely routes of exposure

Inhalation	May cause irritation of respiratory tract.
Eye contact	May cause slight irritation.
Skin Contact	May cause an allergic skin reaction.
Ingestion	May be harmful if swallowed.

#### 11.2 Information on toxicological effects

No information available

### 11.3 Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Not classified.
Serious eye damage/eye irritation	Not classified.
Sensitization	May cause an allergic skin reaction.
Mutagenic effects	Not classified.
1.4 Carcinogenicity	

# 11.4 Carcinogenicity

**Carcinogenicity** No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, OSHA or ACGIH.

#### Legend:

NTP (National Toxicology Program) ACGIH (American Conference of Governmental Industrial Hygienists) IARC (International Agency for Research on Cancer) OSHA (Occupational Safety and Health Administration of the US Department of Labor)

Reproductive Effects	Not classified.
STOT - single exposure	Not classified.
STOT - repeated exposure	Not classified
Aspiration hazard	Not classified.

# 11.5 Acute Toxicity

Unknown acute toxicity 6.27 % of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document

# Product Information (Estimated):

ATEmix (oral)	> 5,000 mg/kg
ATEmix (dermal)	> 2,000 mg/kg
ATEmix (inhalation-dust/mist)	> 5 mg/l

# 12. ECOLOGICAL INFORMATION

12.1 Ecotoxicity Ecotoxicity effects Unknown aquatic toxicity	No known significant effects or critical hazards. Plants and animals may experience harmful or fatal effects when coated with petroleum products. Petroleum-based (mineral) lubricating oils normally will float on water. In stagnant or slow-flowing waterways, an oil layer can cover a large surface area. As a result, this oil layer might limit or eliminate natural atmospheric oxygen transport into the water. With time, if not removed, oxygen depletion in the waterway may be sufficient to cause a fish kill or create an anaerobic environment. 4.74 % of the mixture consists of component(s) of unknown hazards to the aquatic environment
12.2 Persistence and degradability	No information available.
12.3 Bioaccumulation/Accumulation	No information available
12.4. Mobility in soil	No information available
PBT and vPvB assessment	No information available
12.5 Other adverse effects:	No information available

# 13. DISPOSAL CONSIDERATIONS

Hazard characteristic and regulatory waste stream classification can change with product use. Accordingly, it is the responsibility of the user to determine the proper storage, transportation, treatment and/or disposal methodologies for spent materials and residues at the time of disposition.

Waste Disposal Method	This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, o if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whethe the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.		
Contaminated packaging	Dispose of in accordance with local regulations.		
14. TRANSPORT INFORMAT	ION		
DOT - Non bulk	Not regulated		
<u>DOT - Bulk</u>	Not regulated		
ΙΑΤΑ	Not regulated		
IMDG/IMO	Not regulated		

# 15. REGULATORY INFORMATION

### International Inventories

TSCA	All ingredients are on the inventory or exempt from listing
DSL	All ingredients are on the inventory or exempt from listing
NDSL	Not Listed
EINECS	All ingredients are on the inventory or exempt from listing
ELINCS	Not Listed
ENCS	Does not comply
CHINA	All ingredients are on the inventory or exempt from listing
KECL	All ingredients are on the inventory or exempt from listing
PICCS	All ingredients are on the inventory or exempt from listing
AICS	Does not comply
NZIoC	All ingredients are on the inventory or exempt from listing

USA

Federal Regulations

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

#### SARA 311/312 Hazardous Categorization

Acute Health Hazard	Skin Sensitizer
Chronic Health Hazard	Skin Sensitizer
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

#### CERCLA/SARA 302 & 304

Section 302 & 304 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 355.

Chemical Name	CAS No.	Weight-%	RQ	TPQ
Ethylene diamine	107-15-3	<0.01	5000 lb final RQ	10000 lb TPQ
			2270 kg final RQ	
Methyl methacrylate	80-62-6	<0.01	1000 lb final RQ	
			454 kg final RQ	
Benzene	71-43-2	<0.01	10 lb final RQ	
			4.54 kg final RQ	

# Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

Chemical Name	CAS No.	Weight-%	HAPS data
Methyl methacrylate	80-62-6	<0.01	Х
Benzene	71-43-2	<0.01	Х

# CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CAS No.	Weight-%	U.S CWA (Clean

			Water Act)
Zinc alkyl dithiophosphate	68457-79-4	<1	Х
Ethylene diamine	107-15-3	<0.01	Х
Methyl methacrylate	80-62-6	<0.01	Х
Benzene	71-43-2	<0.01	Х

# State Regulations

#### **California Proposition 65**

This product can expose you to a chemical, [Benzene], which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Chemical Name	CAS No.	Weight-%	California Prop. 65		Safe Harbor Limits for Cancer-causing Chemicals (NSRLs)
Benzene	71-43-2	<0.01	Carcinogen Developmental Male Reproductive	24µg/dayoral 49µg/dayinhalation	6.4 μg/day oral 13 μg/day inhalation

#### State Right-to-Know

Chemical Name	CAS No.	New Jersey
Petroleum distillates, solvent-refined heavy paraffinic	64741-88-4	Х
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	Х
Petroleum distillates, hydrotreated light paraffinic	64742-55-8	Х
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	Х
Amines, polyethylenepoly-, reaction products with succinic anhydride polybutenyl derivitives	68439-80-5	Х
Poly long chain alkyl methacrylate	742890923-5216	X

Chemical Name	CAS No.	Massachusetts	
Petroleum distillates, hydrotreated light paraffinic	64742-55-8	Х	

Chemical Name	CAS No.	Pennsylvania
Petroleum distillates, hydrotreated light paraffinic	64742-55-8	Х
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	Х
Amines, polyethylenepoly-, reaction products with succinic anhydride polybutenyl derivitives	68439-80-5	Х
Poly long chain alkyl methacrylate	742890923-5216	Х

**New Jersey Worker and Community Right-to-Know Act:** Under the New Jersey Right-to-Know Act L. 1983 Chapter 315 N.J.S.A. 34:5A-1 et. seq., the product is to be identified as follows: PETROLEUM OIL (Automatic Transmission Fluid)

### Canada

This material has been classified in accordance with the WHMIS 2015 regulation

Chemical Name	CAS No.	Weight-%	NPRI

Methyl methacrylate	80-62-6	<0.01	Listed
Benzene	71-43-2	<0.01	Listed

Legend

NPRI - National Pollutant Release Inventory

16. OTHER INFORMATION				
	NFPA_	Health: 2	Flammability: 1	Instability: 0
Prepared By		Lakyn Neumeyer		
Revision Date:		31-May-2017		
<b>Revision Summary:</b>		New product number		

**Disclaimer:** 

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet